



GST86-22L/A

Floor Ceiling

Parameter



Anti cool
air design



Humanized
sleep function



Memory
function



Independent
dehumidification
system



Rapid cooling
(heating)



Intelligent
defrosting



Low
voltage startup



Low temperature
startup

R22

Model	Power supply	Function	Capacity (Btu/h)	Power input (W)	EER/C.O.P (W/W)	Indoor unit (W×H×D)				Airflow (m ³ /h)	Outdoor unit (W×H×D)				Loading quantity	
						Body size (mm)	Package size(mm)	N.W/G.W (kg)	Noise dB(A)		Body size (mm)	Package size(mm)	N.W/G.W (kg)	Noise dB(A)	40' GP	40' HQ
GST24-22L/A	1Ph 220V 60Hz	Cooling	24000	2800	2.50	1300 × 600 × 188	1414 × 724 × 248	32/36	49	1140	1018 × 840 × 412	1100 × 905 × 450	75/80	59	82	91
GST24-22R/A		Cooling	24000	2800	2.50											
		Heating	28700	2800	3.00											
GST36-22L/A	3Ph 220V 60Hz	Cooling	36000	4200	2.51	1590 × 695 × 238	1770 × 830 × 330	42/53	49	2100	1040 × 840 × 410	1100 × 880 × 450	90/105	62	50	58
GST36-22R/A		Cooling	36000	4200	2.51											
		Heating	37500	3800	2.89	1590 × 695 × 238	1714 × 830 × 330	42/51	57	2100	1032 × 1250 × 412	1110 × 1280 × 450	112/133	64	45	52
GST42-22L/A		Cooling	42000	5900	2.03											
GST42-22R/A		Cooling	42000	5300	2.26											
		Heating	46100	4900	2.76											
GST60-22L/A	3Ph 220V 60Hz	Cooling	60000	8350	2.11	1590 × 695 × 238	1714 × 830 × 330	42/51	58	2300	1032 × 1250 × 412	1110 × 1280 × 450	125/146	65	45	52
GST60-22R/A		Cooling	60000	8350	2.11											
		Heating	50000	6800	2.33	2300 × 780 × 330	2420 × 1055 × 530	125/205	58	3200	990 × 1700 × 840	1162 × 1900 × 1012	230/245	63	12	12
GST86-22L/A		Cooling	86000	9500	2.65											

Model	Power supply	Function	Capacity (Btu/h)	Power input (W)	EER/C.O.P (W/W)	Indoor unit (W×H×D)				Airflow (m ³ /h)	Outdoor unit (W×H×D)				Loading quantity	
						Body size (mm)	Package size(mm)	N.W/G.W (kg)	Noise dB(A)		Body size (mm)	Package size(mm)	N.W/G.W (kg)	Noise dB(A)	40' GP	40' HQ
GST36-38L/A	3Ph 380V 60Hz	Cooling	36000	4350	2.43	1590 × 695 × 238	1770 × 830 × 330	42/53	52	2100	1040 × 840 × 410	1100 × 880 × 450	90/105	62	50	58
GST36-38R/A		Cooling	36000	4350	2.43											
		Heating	37500	3900	2.82	1590 × 695 × 238	1714 × 830 × 330	42/51	57	2100	1032 × 1250 × 412	1110 × 1280 × 450	112/133	64	45	52
GST42-38L/A		Cooling	42000	6000	2.00											
GST60-38L/A		Cooling	60000	8000	2.20											
GST60-38R/A		Cooling	60000	8380	2.10											
	Heating	50000	7000	2.60												

Note: For technical improvement, the specifications, designs and information in this catalogue are subject to change without notice.

The specifications, designs and information on this website are subject to change without notice; and specifications may be different between different markets, please consult your local dealer/distributor for details.